

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Revised On 03/14/2017

1 Identification

Trade name: ATHLETIC FIELD RED
Product code: 0000200643
Distributed by: Fast line Striping Systems Ltd.
 34 Mount Hope Avenue
 Dartmouth NSB2Y 4K9
 Canada
 Phone: 1-800-565-1564
 Fax: 1-902-466-8481
 admin@fastline.net

General Information: Health & Safety Department
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard identification

Classification of the substance or mixture

Flammable Aerosols - Category 1 H222 Extremely flammable aerosol.
 Gases Under Pressure - Liquefied Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irritation - Category 2 H315 Causes skin irritation.

GHS Hazard pictograms



GHS02 GHS04 GHS07

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Protect from sunlight. Store in a well-ventilated place.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate Specific Target Organ Toxicity - Single Exposure - Category 3, H335	13.4% w/w
74-98-6	propane Flammable Gases - Category 1, H220	12.6% w/w
106-97-8	n-butane Flammable Gases - Category 1, H220	7.4% w/w
64742-89-8	VM&P Naphtha Flammable Liquids - Category 2, H225	6.51% w/w
142-82-5	heptane Flammable Liquids - Category 2, H225; Skin Irritation - Category 2, H315; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	6.28% w/w
64742-47-8	Mineral Spirits Flammable Liquids - Category 3, H226; Aspiration Hazard - Category 1, H304	5.78% w/w
1330-20-7	xylene (mix) Flammable Liquids - Category 3, H226; Acute Toxicity (Dermal) - Category 4, H312; Acute Toxicity (Inhalation) - Category 4, H332; Skin Irritation - Category 2, H315	5.48% w/w
2425-85-6	Red Pigment Specific Target Organ Toxicity - Single Exposure - Category 3, H335	1.61% w/w
100-41-4	ethyl benzene Flammable Liquids - Category 2, H225; Aspiration Hazard - Category 1, H304; Acute Toxicity (Inhalation) - Category 4, H332	1.03% w/w

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Revised On 03/14/2017

Trade name: ATHLETIC FIELD RED

(Contd. of page 1)

Information for doctor:**Most important symptoms and effects:**

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Firefighting measures**Extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Fire/explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Conditions for safe storage:**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/ Personal protection**Components with limit values that require monitoring at the workplace:****74-98-6 propane**

EL Long-term value: 1000 ppm

EV Long-term value: 1.000 ppm

106-97-8 n-butane

EL Short-term value: 750 ppm

Long-term value: 600 ppm

EV Long-term value: 800 ppm

142-82-5 heptane

EL Short-term value: 500 ppm

Long-term value: 400 ppm

EV Short-term value: 2.045 mg/m³, 500 ppmLong-term value: 1.635 mg/m³, 400 ppm**64742-47-8 Mineral Spirits**EL Long-term value: 200 mg/m³

Skin

1330-20-7 xylene (mix)

EL Short-term value: 150 ppm

Long-term value: 100 ppm

EV Short-term value: 650 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppm**100-41-4 ethyl benzene**

EL Long-term value: 20 ppm

IARC 2B

EV Short-term value: 540 mg/m³, 125 ppmLong-term value: 435 mg/m³, 100 ppm**Exposure controls****Hygienic protection:**

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves

Nitrile gloves.

Eye protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles

9 Physical and chemical properties**Appearance:**

Aerosol.

(Contd. on page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 03/14/2017

Revised On 03/14/2017

Trade name: ATHLETIC FIELD RED

(Contd. of page 2)

Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C
Flash point:	-19 °C
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	45.5 %
Water:	30.0 %
MIR Value:	0.69
Solids content:	23.2 %

10 Stability and reactivity

Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Possibility of hazardous reactions:	No dangerous reactions known.
Conditions to avoid	No further relevant information available.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

1330-20-7 xylene (mix)

Oral LD50 8700 mg/kg (rat)

Dermal LD50 2000 mg/kg (rbt)

Inhalative LC50/4 h 6350 mg/l (rat)

2425-85-6 Red Pigment

Oral LD50 >5000 mg/kg (rat)

100-41-4 ethyl benzene

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rbt)

Skin effects:	No irritant effect.
Eye effects:	No irritating effect.
Sensitization:	No sensitizing effects known.

IARC (International Agency for Research on Cancer)

1330-20-7	xylene (mix)	3
2425-85-6	Red Pigment	3
100-41-4	ethyl benzene	2B

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Ecotoxicological effects:	
Remark:	Toxic for fish
Other adverse effects:	No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

(Contd. on page 4)

Safety Data Sheet
according to HPR, Schedule 1

Printing date 03/14/2017

Revised On 03/14/2017

Trade name: ATHLETIC FIELD RED

Recommendation: Completely empty cans should be recycled.

(Contd. of page 3)

14 Transport information

UN-Number	UN1950
DOT	N/A
Transport hazard class(es):	
DOT, TDG	
Class	2.1
Marine pollutant:	Symbol (fish and tree)
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Packaging Group:	Not applicable. --

15 Regulatory information

Toxic Substances Control Act (TSCA): All ingredients for this product are found on the inventory list of substances.

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL PROTECTION ACT: WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
A - Compressed gas



Canadian WHMIS: Chemical safety assessment:

D2A
A Chemical Safety Assessment has not been carried out.

16 Other information

Contact: Regulatory Affairs