Safety Data Sheet according to HPR, Schedule 1

Printing date 03/14/2017 Revised On 03/14/2017

1 Identification

Trade name: **ALERT ORANGE** Product code: 0000200670

Distributed by:

Fast line Striping Systems Ltd. 34 Mount Hope Avenue Dartmouth NSB2Y 4K9 Canada Phone: 1-800-565-1564 Fax: 1-902-466-8481 admin@fastline.net

Health & Safety Department **General Information:**

CHEMTEL 1-800-255-3924, or 813-248-0585. **Emergency telephone number:**

2 Hazard identification

Classification of the substance or mixture

Flammable Aerosols - Category 1 H222 Extremely flammable aerosol.

Gases Under Pressure - Liquefied Gas H280 Contains gas under pressure; may explode if heated.

Specific Target Organ Toxicity - Single Exposure - Category 3 H335 May cause respiratory irritation.

GHS Hazard pictograms

GHS02 GHS04 GHS07

Signal word Danger

Hazard-determining components of

labeling:

Calcium Carbonate titanium dioxide

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause respiratory irritation.

Precautionary statements If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area.

Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also

damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
74-98-6	propane	Flammable Gases - Category 1, H220	17.64% w/w
64742-89-8	VM&P Naphtha	Flammable Liquids - Category 2, H225	17.06% w/w
1317-65-3	Calcium Carbonate	Specific Target Organ Toxicity - Single Exposure - Category 3, H335	15.34% w/w
	n-butane	Flammable Gases - Category 1, H220	10.36% w/w
64742-47-8	Mineral Spirits	Flammable Liquids - Category 3, H226; Aspiration Hazard - Category 1, H304	4.52% w/w

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact: After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse mouth with water. Do not induce vomiting.

After swallowing: Information for doctor:

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Firefighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet according to HPR, Schedule 1

Revised On 03/14/2017 Printing date 03/14/2017

Trade name: ALERT ORANGE

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Environmental precautions:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Do not allow product to reach sewage systems or ground water.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Fire/explosion protection:

Use only in well ventilated areas.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50

°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from

electrostatic discharges.

Conditions for safe storage:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing Storage requirements:

conditions. Store locked up.

8 Exposure controls/ Personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

EL Long-term value: 1000 ppm EV Long-term value: 1.000 ppm

106-97-8 n-butane

EL | Short-term value: 750 ppm Long-term value: 600 ppm EV Long-term value: 800 ppm

64742-47-8 Mineral Spirits

EL Long-term value: 200 mg/m³ Skin

Exposure controls

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Protective gloves Hand protection:

Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined.

Boiling point: -44 °C -19 °C Flash point:

Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

VOC content (less exempt solvents): 51.0 % Water:

24.0 %

(Contd. on page 3)

Safety Data Sheet according to HPR, Schedule 1

Printing date 03/14/2017 Revised On 03/14/2017

Trade name: ALERT ORANGE

(Contd. of page 2)

Solids content: 23.9 %

10 Stability and reactivity

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid No further relevant information available. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must

be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A

Transport hazard class(es):

DOT, TDG

Class

Warning: Gases Special precautions for user:

EMS Number: F-D,S-U

Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For MASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code Not applicable.

Packaging Group:

15 Regulatory information

Toxic Substances Control Act

All ingredients for this product are found on the inventory list of substances. (TSCA):

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

WHMIS Symbols for Canada: Compressed gas

A Chemical Safety Assessment has not been carried out. Chemical safety assessment:

16 Other information

Contact: Regulatory Affairs